



Blu-Tack Colour

THE ORIGINAL RE-USABLE ADHESIVE

YOUR SMART ADVANTAGES

- Permanently plastic and pliable
- Reusable
- Australian made
- Non-toxic, suitable for the family
- Tested in accordance to AS/NZS ISO 8124:2012 (Safety of Toys – Part 3)

USES

Bostik Blu-Tack® Colour is a permanently plastic, reusable multipurpose adhesive. Blu-Tack® is supplied in the form of rectangular strips between sheets of release paper and packed in individual envelopes. Bostik Blu-Tack® is clean and economical in use.

Blu-Tack® Colour has a myriad of uses around the home, office, school, factory or workshop.

Create 3D models or fantastic murals on your window or wall. Holds up posters, cards, children's paintings, party decorations, maps, messages, etc. Telephones and calculators to desks, ornaments to shelves, photos in albums, screws to screwdrivers, model parts during painting, etc.

Holds safety pins, keys, screws, etc. flowers and candles in place for table and flower arrangements.

Cleans fluff from fabric and dirt from typewriters, model railway tracks, etc. May be rolled and manipulated to make 3 dimensional artistic 'models'.

For use on non-porous surfaces: - vinyl coated wallpapers, painted surfaces, glass, and metal.

PRODUCT CHARACTERISTICS

Colours	Green, pink, blue, orange & yellow
Form	Putty Strips
Composition	Synthetic Polymer Base
Specific Gravity	1.9 approx.
Pack Quantity	10 units



TYPICAL PERFORMANCE DATA (approx.)

Solubility Insoluble

DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the relevant QR code on pack.

SURFACE PREPARATION

1. Wash hands before use.
2. Ensure surfaces are clean; dry free from grease and loose materials.

APPLICATION

Blu-Tack® Colour works because its pressure sensitive.

1. For non-laminated surfaces make a blob by tearing off a piece, pull and stretch into a ball and apply to one surface.
2. For laminated surfaces cut off 3-5cm pieces of Blu-Tack, remove the release paper on one side, apply to one surface, then remove the other release paper.
3. Using good thumb pressure, apply to the other surface.

REMOVAL

To remove Blu-Tack® Colour, hold and twist off or roll it carefully off the surface. Any remaining shreds can be removed by rolling or dabbing a blob of Blu-Tack over the surfaces.

STORAGE AND SHELF LIFE

Store away from heat, strong oxidizing agents and acids. Store between 5°C to 30°C. Shelf life is 5 years from the date of manufacture when stored as directed.

BOSTIK BLU-TACK® COLOUR

HEALTH & SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at www.bostik.com.au

PRECAUTION IN USE

Do not use Blu-Tack® Colour on absorbent, silk screen printed or hand stencilled wallpaper nor on porous brickwork.

Care should be taken on painted plaster as Blu-Tack® Colour's adhesive qualities may cause paint to come away from wall.

The adhesive properties of Blu-Tack Colour increase over time, so take extra care when removing after a period of months. On some surfaces Blu-Tack Colour can leave an oily mark but this can often be removed using De-Solv-It Sticky Spots, Stain Remover or lighter fluid. Before using these products, we recommend you test on a small inconspicuous area.

Not suitable to support heavy objects. 0.5g holds 105g of load.

FIRE

Non-flammable.

Recommendations and suggestions are for guidance only, since conditions of use are completely out of our control.

DISCLAIMER:

The information in this Technical Data Sheet is intended for the assistance of users and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge and control. Users are asked to make sure that the TDS in their possession is the latest issue. Likewise, we recommend users carry out their own tests to determine the suitability of the product for their particular purposes.

Any claim for a defective product must be filed within 30 days of discovery of a problem and must be submitted with written proof of purchase. Claims are not transferrable or assignable and extend only to the original purchaser/user. Bostik reserves the right to inspect and alleged failure and no responsibility will be accepted unless Bostik is given the opportunity to do so. Bostik limits its liability to the replacement of the product/s proven faulty.

BOSTIK PHILIPPINES, INC.

35/F Penthouse Raffles Corporate Center
F. Ortigas Jr. Road, Ortigas Business Center
Pasig City Philippines
Tel No: +632 7900 5633 | Fax: +632 7900 5626

BOSTIK HOTLINE

Smart help +632 7900 5656

