

Silicone Stripper

SILICONE REMOVER

TECHNICAL DATA SHEET

SMART ADVANTAGES

- REMOVES CURED SILICONE
- SAG RESISTANT
- LOW ODOUR

DESCRIPTION

Bostik Silicone Stripper is a unique, technologically advanced paste, formulated to easily and safely remove fresh or old silicone sealant from a variety of substrates e.g. sanitary-ware, glass, metal, enamel, concrete, plaster, plastics and textiles.

APPLICATIONS

Removing cured silicone from a surface in order to prepare the surface for a fresh application of silicone. Ideal for removing cured silicone smudges, spills and finger prints from poor workmanship. Bostik Silicone Stripper can also be used to remove mould growth from the surface of silicones.

LIMITATIONS

- May stain some metal surfaces. We recommend testing a small area prior to application.
- May cause wood substrates to darken.
- May soften painted or varnished surfaces and some fabrics (e.g. Nylon).

SAFETY INSTRUCTIONS

Bostik Silicone Stripper is flammable. Always work in a ventilated area. Do not breathe in vapours. Avoid exposing product to any ignition sources. Do not smoke when working with Bostik Silicone Stripper. It is advisable to wear gloves in order to avoid direct contact with the skin. If product comes in to contact with skin or eyes, rinse thoroughly and immediately with water. Seek medical attention if irritation or discomfort persists. Keep out of reach of children! Refer to our Safety Data Sheets for further toxicological information and comprehensive handling instructions.

SURFACE PREPARATION

Protect areas that are not covered in silicone with tape in order to reduce risk of staining.

HOW TO USE

1. Removing excess silicone with a knife or blade will reduce the stripping time.
2. Remove cap from tube and pierce seal with reverse side of cap.
3. Apply a thick layer of Bostik Silicone Stripper to the desired area and leave for 2 to 12 hours, depending on the thickness of the silicone.
4. Covering with a plastic sheet will enhance performance.
5. Remove softened sealant with a hard plastic scraper or spatula.
6. Thin films can simply be wiped away with a damp cloth.
7. Reapplication may be needed for thicker silicone layers.

CLEANING

Bostik Silicone Stripper can be cleaned with Turpentine, Paraffin or Water.



STORAGE STABILITY

Bostik Silicone Stripper has a shelf life of at least 12 months if stored in a cool (below 25°C), dry place in its original moisture-tight container. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable.

PRODUCT PACKAGING

- 90ml Tube

PRODUCT DATA	
Appearance	Homogenous brown paste
Softening time	Approx. 1 – 12 hours
Heat Resistance	35°C
Cold Resistance	0°C
Coverage (90ml)	Approx. 4 meters

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400
Beverly Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
www.bostik.co.za

ASK A STICKY QUESTION...

www.stickyquestions.co.za
0800 222 400

