

Crystal Clear Tape

ULTRA TRANSPARENT TAPE

TECHNICAL DATA SHEET

SMART ADVANTAGES

- ULTRA-TRANSPARENT, CRYSTAL CLEAR ON MOST SURFACES
- DURABLE METAL BLADE FOR PRECISION CUTTING
- RESISTANT TO AGING, NON-YELLOWING
- ACID FREE, IDEAL FOR SCRAP BOOKING

DESCRIPTION

Bostik Crystal Clear Tape is an ultra-transparent, pressure-sensitive polypropylene tape exhibiting an excellent balance of tack and peel properties to give optimum adhesive strength. Its crystal clear properties make this tape ideal for gift wrapping. Bostik Crystal Clear Tape is packaged in a strong, easy to use dispenser with a durable metal blade for precision cutting.

APPLICATIONS

Ideal home, office and school, where it can be used for gift wrapping, sealing of boxes, holding up posters, labelling of files, art and crafts, scrap booking, photo albums, handicraft, decorative work and temporary repairs.

ADHESION

Bostik Crystal Clear Tape bonds to most materials like paper, card, foil, glass, metal, wood and plastics.

LIMITATIONS

- Not for heavy duty use.
- May damage fragile papers on removal.
- Not suitable where heat resistance is required.

SAFETY INSTRUCTIONS

Use dispenser with caution as it contains a sharp edge. Keep out of reach of small children! Does not contain natural rubber latex.

SURFACE PREPARATION

Ensure that surfaces are clean, dry and free of any dust, grease and loose materials.

HOW TO USE

1. Pull tape to desired length and cut with the serrated edge of the dispenser.
2. Apply to surfaces and press firmly over the entire area.

CLEANING

Easily removed from most surfaces. Adhesive residue can be removed with acetone from non-porous surfaces.

STORAGE STABILITY

The shelf life of the product is 36 months when stored at room temperature.

PRODUCT PACKAGING

Bostik Crystal Clear Tape Dispenser (18mm x 20m)



TECHNICAL DATA SHEET

PRODUCT CHARACTERISTICS	
Adhesive	Solvent based pressure-sensitive acrylic
Appearance	Clear sticky tape
Film type	Biaxial orientated polypropylene
Film thickness	50 μ
pH	7 – 8

TYPICAL PERFORMANCE DATA	
Temperature resistance	-10 to 60°C
Tensile strength	>72 N/25mm [GB/T7753-1987]
Peel Adhesion (180°)	>3.4 N/25mm [GB/T2792-1998]
Water resistance	Good

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400
Beverly Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
www.bostik.co.za

ASK A STICKY QUESTION...

www.stickyquestions.co.za
0800 222 400

