

Double Sided Tape

PAPER THIN & EASY TO TEAR

TECHNICAL DATA SHEET

SMART ADVANTAGES

- DOUBLE SIDED, IDEAL ALTERNATIVE TO GLUE
- PAPER THIN INVISIBLE GLUE LINE
- AGGRESSIVE TACK, INSTANT HOLD
- EASY TO TEAR, NO SCISSORS REQUIRED

DESCRIPTION

Bostik Double Sided Tape is an acid free, high quality, paper thin, double sided tape with aggressive tack that is easy to tear – no scissors required. Ideal for non-visible attachment of posters and photos. The double sided tape is an ideal alternative to glue.

APPLICATIONS

Ideal home, office and school work, where it can be used for gift wrapping, sealing of boxes, holding up posters, labelling of files, art and crafts, scrap booking, photo albums, handicraft, decorative work, invisible fixing and temporary repairs for example, on hems.

ADHESION

Bostik Double Sided Tape bonds to most materials like paper, card, foil, glass, metal, wood and plastics.

LIMITATIONS

- Not for heavy duty use.
- May damage fragile papers on removal.
- Not suitable where heat resistance is required.

SAFETY INSTRUCTIONS

Keep out of reach of small children! Does not contain natural rubber latex.

SURFACE PREPARATION

Ensure that surfaces are clean, dry and free of any dust, grease and loose materials.

HOW TO USE

1. Measure and tear off the desired length of tape.
2. Stick the tape flat against one surface ensuring there are no wrinkles.
3. Remove the protective white layer from the tape and discard.
4. Align the surfaces and gently press together. Once surfaces meet, the tape is not repositionable.

CLEANING

Easily removed from most surfaces non-porous surfaces. Adhesive residue can be removed with acetone.

STORAGE STABILITY

The shelf life of the product is 36 months stored at room temperature.

PRODUCT PACKAGING

Bostik Double Sided Tape Roll 18mm x 10m



TECHNICAL DATA SHEET

PRODUCT CHARACTERISTICS	
Adhesive	Hotmelt PSA
Appearance	White sticky tape
Film type	Tissue paper
Film thickness	210 μ
pH	7 – 8

TYPICAL PERFORMANCE DATA	
Temperature resistance	-10 to 60°C
Tack	>8 [GB/T2792-1998]
Tensile strength	>35 N/25mm [GB/T7753-1987]
Peel Adhesion (180°)	>10.0 N/25mm [GB/T2792-1998]
Water resistance	Good

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400
Beverley Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
www.bostik.co.za

ASK A STICKY QUESTION...

www.stickyquestions.co.za
0800 222 400

