

NAIL IT FAST CURE POWERFUL INSTANT GRAB ACRYLIC DECORATORS ADHESIVE

TECHNICAL DATA SHEET

BENEFITS

- Solvent free
- Suitable for EPS and XPS
- Almost odourless
- Easy to apply and clean
- Non corrosive towards metal

PRODUCT DESCRIPTION

Bostik NAILIT FAST CURE is a versatile adhesive based on acrylic dispersion. The adhesive cures due to evaporation of water to form a strong and durable bond.

APPLICATIONS

Bostik NAIL IT FAST CURE was specifically developed for bonding wood, chipboard, hardboard and uPVC to brick work, stone or concrete. Also suitable for EPS and XPS and bonding ceramic tiles to porous substrates. For interior use.

DIRECTIONS OF USE

Apply as an adhesive in a 'ventilating' way in vertical stripes or dots with 20 – 40 cm distance in between stripes. The material must be put into place by shoving and pushing firmly. For further questions, please consult our technical department.

TECHNICAL DATA		
Application		+5°C to +40°C
temperature		
Base		Acrylic Dispersion
Curing time	@ +23°C/50% RH	3 days
Density	ISO 1183-1	1,90 g/ml
Frost resistance during		Up to - 15°C
transportation		
Open Time	@ +23°C/50% RH	5-10 min
Temperature		-20°C to + 75°C
resistance		
Usage		600 mL/m ²

These values are typical properties and may vary +/-3%

LIMITATIONS

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

- Not suitable for continuous exposure to water
- Not suitable for movement joints

SURFACE PREPARATIONS AND FINISHING

Application temperature + 5°C to + 40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Substrates to be cleared of all loose particles, absorbent substrates do not need to be absolutely dry. Very porous substrates like: gypsum, aerated concrete, limestone, etc, need to be primed with a mixture of 1 part Bostik NAIL IT FAST CURE and 2 parts water. Always test adhesion prior to application. Finish and smooth with water.

CLEANING

Uncured material and tools can be cleaned using water or Methylated Spirit. Cured material can only be mechanically removed. Hands can cleaned with **Bostik HANDY WIPES.**

COLOUR(S)

- White

PACKAGING

- 300mL Cartridge, 12 per box

SHELF LIFE

In unopened original packaging between + 5° C and + 25° C, shelf life is up to 18 months from production date, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

CERTIFICATIONS

- A+ French VOC Regulation

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au

Bostik Australia

Level 1, 6 English Street, Essendon Fields, Victoria, Australia 3041 T.: 1800 267 845 www.bostik.com.au

Bostik Sealing & Bonding Technical Data Sheet_KITCHEN & BATHROOM SILICONE CLASSIC_DEC2021

