



# Bostik Heavy Duty Mounting Tape Roll

## REPAIR AND ASSEMBLY

TECHNICAL SHEET 25/04/2024

### SMART ADVANTAGES

- Double sided – Ideal alternative to glue
- Aggressive tack – Instant hold
- Acid free – Safe for posters, photos or gifts
- Heavy Duty – Strong enough to attach mirrors
- Double thickness – Better adhesion to mildly uneven surface like plaster wall or painted wall

### DESCRIPTION

Bostik Heavy Duty Mounting Tape Roll is an everyday, double sided self-adhesive tape, ideal for mirror tiles, framed pictures and more.

### APPLICATIONS

- It is ideal for use on a variety of smooth surfaces such as tiles, metal, wood, board, stone, glass, fiberglass and some plastics.
- It is suitable for interior and exterior use.

### ADHESION

Tiles, wood, metal, stone, glass, synthetics, paper, card, foil and certain plastics.

### LIMITATIONS

- Not for objects of value.
- Not for use on rough or crumbly surfaces.
- Not for use above bed.
- Not suitable where heat resistance is required.

### SAFETY INSTRUCTIONS

- Bostik Heavy Duty Mounting Tape does not cause skin irritation to individuals with normal skin sensitivity.
- Keep Bostik Heavy Duty Mounting Tape out of reach of small children and pets!
- Refer to our Material Safety Data Sheets for further toxicological information and comprehensive handling instructions.



### SURFACE PREPARATION

- Surfaces should be dry and free of dust, dirt and grease.

### DIRECTIONS FOR USE

- Ensure surfaces are smooth, clean, dry and free of dust, grease and any loose material.
- Peel off and cut the length of tape to be used.
- Press the sticky side of the tape firmly onto the object to be mounted or secured.
- Remove the wax paper and position the object into place.
- Apply firm pressure onto the object for at least 60 seconds.
- Final holding strength will be achieved after 24 hours.

### CLEANING

- Product must be removed mechanically. Any adhesive residue can be removed with acetone.

### STORAGE STABILITY

The shelf life of the product is 36 months stored at room temperature.

### PRODUCT PACKAGING

- 10m x 24mm x 3mm

## PRODUCT CHARACTERISTICS

Appearance	White sticky tape
Carrier	Polyethylene
Carrier thickness	3mm
Adhesive	SIS synthetic rubber, phenylethylene, methyl and butadiene
pH	7 - 8
Holding strength	Up to 1.5cm <sup>2</sup> per kg tested on a stainless steel surface in lab conditions at room temperature
Heat resistance	Good
Water resistance	Good

### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

**Bostik South Africa**  
Beverley Close, Montague Gardens, 7441  
Head Office: +27 21 555 7400  
[diy.bostik.com/en-ZA](http://diy.bostik.com/en-ZA)

**BOSTIK HELPLINE**

Smart help +27 800 222 400



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.