



# Breathe

## HUMIDITY ABSORBER (INCLUDING 2X250G TABLETS)

TECHNICAL SHEET NO: TDS02242 07/11/2023

### SMART ADVANTAGES

- +33% higher moisture absorption than the market average
- Made using recycled plastic and food industry waste
- Colourant and perfume free

### DESCRIPTION

Bostik Breathe is a noise-free, chemical-based humidity absorber that absorbs moisture in the air and prevents condensation issues. Bostik Breathe fits in all home spaces, suitable for use in; bathroom, kitchen, laundry rooms, bedrooms, living rooms.

Bostik Breathe does not require electricity and absorbs moisture through chemical-based unique tablets, which contain no colourants, perfumes or any other additives. The tablets absorb moisture from the air and convert into a liquid solution which is collected in the tank.

The two tablets total to 500g, covering rooms up to 25m<sup>2</sup> and will last up to 4 months depending on humidity levels in the room. The two-tablet system offers up to 33% higher moisture absorption and 11% additional tablet weight than the market average. One tablet can also be used for smaller sized rooms up to 12m<sup>2</sup>.

The unit is both sustainable and efficient; being made from recycled plastic and food industry waste with an easy-pour spout, spillproof seal and a 1.2l tank capacity. Making it safe and easy for emptying, cleaning and transportation.



### TECHNICAL CHARACTERISTICS

Colour	Cream & Transparent
Form	Calcium Chloride
Composition	Hydrocarbon Polymer
Coverage	Two tablets cover rooms up to 25m <sup>2</sup> , one tablet covers rooms up to 12m <sup>2</sup>
Tablet life	Up to 4 months *dependent on humidity levels

### APPLICATION

**IMPORTANT:** Before using Bostik Breathe refer to the relevant Health & Safety Data Sheet, available at [www.bostik.co.uk](http://www.bostik.co.uk).

### APPLICATION

- Lift the unit cover and take the two tablets still wrapped in their covering and open them on one side.
- Insert the tablets into their shelves between the provided pitches. Ensure to avoid any skin contact.
- Close the lid, you now have a working humidity absorber.

### CLEANING

- Lift the top canister housing.
- Empty the liquid solution into the sink or toilet.

- The absorber can be fully disassembled to allow for cleaning and easily reassembled.

#### STORAGE

- Store at a temperature level not exceeding 40°C. Store for up to 24 months from the date of manufacture. The liquid solution can stain and damage certain materials such as fabric, leather and metals. In case of contact, rinse with lukewarm water immediately.

#### PRECAUTIONS IN USE

To optimise absorption, place in location exposed to air circulation. To avoid the risk of the unit falling and spillage, please place in an area which avoids the danger of being knocked over.

Refills should be replaced once fully dissolved so the absorber continues to operate.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.co.uk](http://www.bostik.co.uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Breathe Humidity Absorber, available at [www.bostik.co.uk](http://www.bostik.co.uk).

#### PACKAGING

Product codes	30624757	Bostik Breathe Humidity Absorber
---------------	----------	----------------------------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>

#### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.