

# Leather Repair Clear Glue

## SOLVENT-BASED POLYURETHANE CEMENT

Date: 11 August 2020

Fact Sheet No.: TDS00206

### YOUR SMART ADVANTAGES

- Ultra strong, long lasting and flexible bond
- Water resistant
- Formulated to work on leather and imitation leather

### USES

Bostik Leather Repair Clear Glue is a general purpose, solvent-borne adhesive, the dried film of which is virtually colourless and non-staining. It is quick drying, clean to use and provides strong, water-resistant bonds with excellent aging properties.

Bostik Leather Repair Clear Glue will bond a wide variety of materials including metals, wood, glass, china, leather, felt, canvas, paper, cardboard, certain fabrics, PVC and some other plastics. It will bond all these materials to themselves or to each other and also plaster, stone and concrete.

Bostik Leather Repair Clear Glue is suitable for many assembly and repair applications in and around the home and other locations. Typical items on which it is used are handbags, luggage, lampshades, picture frames, upholstery, jewellery, books, china and marquetry pieces.

### PRODUCT CHARACTERISTICS

Colour	Colourless
Form	Mobile liquid
Specific Gravity	0.9 approx.
Composition	Polyurethane rubber/resin based solution
Product Code	30803758 20ml blister cards x 6

Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +15°C to +25°C.
Odour	Ketonic
Solvent	Mixture of butanone and acetone
Viscosity	Approx. 3.3 Pa s (33 poise) at 20°C
Solids Content	25% (in tubes)
Drying Time	5 minutes, approx. at 23°C (RT)
Support Time	20 to 30 minutes at RT
Handling Time	1 to 2 hours

### TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Flammability	Highly flammable
Flash Point	(Closed Cup) in the group -18°C to +7°C.
Temperature Resistance	Resists from -40°C to +80°C.
Water Resistance	Good
Petrol Resistance	Good, but will not withstand prolonged immersion
Solvent Resistance	Good to intermittent contact with alcohols. Not resistant to ketones and esters.
Dilute Acid & Alkali	Good resistance

## DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Leather Repair Clear Glue refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

## PREPARATION

1. Work on a protected area as spills can damage sensitive surfaces, such as polished, cellulose surfaces and fabrics.
2. Make sure that the surfaces to be bonded are clean, dry and free from dust, dirt and grease.
3. When bonding leather avoid spills onto the shiny side as a mark will be left.

## APPLICATION

4. To bond non-absorbent surfaces such as metal or glass apply a thin film of adhesive to both surfaces. Allow 5 to 10 minutes drying time and then, having correctly positioned the surfaces, press them together firmly. The bond will be instant and non-adjustable.
5. If one or both surfaces are absorbent apply a generous film of adhesive to one surface only and immediately join the two surfaces together under pressure.

NOTE: Using this technique, initial bond strengths will be lower.

## CLEANING

6. Remove surplus adhesive by the use of nail varnish remover or acetone.

## PRECAUTIONS IN USE

Do not use Bostik Leather Repair Clear Glue on polythene, polypropylene, polystyrene & cellulose paint, rayon and acetate fabrics. Also, it is not suitable for repairing pottery handles or other items that may contain hot liquids.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Leather Adhesive, available at [www.bostik.com/uk](http://www.bostik.com/uk).

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>